



Identify what matters

Zenius



FLEXIBILITY

SMALL
FOOTPRINT

EASE-OF-USE



PRINTER

The Compact and Agile Card Printer

The **Zenius** printer is designed for single sided printing and encoding of a very large variety of plastic cards. Zenius generates color or monochrome cards, individually or in small runs, with top quality results.

Zenius is a user-friendly, compact and cost-effective solution for delivering your personalized cards.




Flexibility

- With Zenius, you can choose to insert your cards individually or with the automatic feeder.
- The **«Expert» version** of Zenius features **combinable encoding functions**: magnetic encoding, contact and contactless chips. It takes just a few minutes to install these modules!




Ease of Use

- With the **Evolis Premium Suite® software**, you can receive notifications and easily control the printer from your computer.
- Evolis High Trust® ribbons** are easy to install and automatically recognized and set by the printer.



Small Footprint

- Hardly larger than a standard sheet of paper, Zenius fits perfectly into any environment, be it the office or a customer service counter.
- Zenius is an eco-designed printer: very efficient sleep mode and low energy consumption.



ZENIUS

- Manual or automatic card feeder

- Easy handling, automatic ribbon recognition and setup!

Main Features

Full technical specifications
on www.evolis.com

General Features

- Direct-to-card dye-sublimation/ Resin thermal transfer
- Single-sided printing, edge-to-edge
- 300 dpi print head (11.8 dots/mm)
- 16 million colors
- 16 MB memory (RAM)

Printing Performances

- Color (YMCKO): 120 - 150 cards/hour¹
- Monochrome: 400 - 500 cards/hour

Interfaces

- USB (1.0, 1.1, 2.0, 3.0), cable supplied
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led) on the Expert version

Card Management & Specifications

- Automatic or manual feeding
- Feeder capacity: 50 cards (0.76 mm – 30 mil)
- Output hopper capacity: 20 cards (0.76 mm – 30 mil)
- Card thickness: 0.25 to 0.76 mm (10 to 30 mil), gauge adjustment
- Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)

Optional Features

- Colors available: fire red & grey brown
- Expert version: Ethernet TCP-IP, encoding modules as options

Additional Encoding Modules

- Available modules:
 - Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
 - Smart contact station ISO 7816-2
 - Contact smart card encoder - PC/SC, EMV 2000-1
 - Contactless smart card encoder - ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS
 - Other specific encoders upon request
- Internal USB or IP ports
- Options can be combined
- Factory-installed or installed on site

Safety

- Support for Kensington® security lock
- Data encryption for magnetic encoding

Display

- Printer LEDs
- Graphical notifications from the printer²: cleaning alerts, empty/low level ribbon and card alerts, etc.

Evolis High Trust® Ribbons

To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- Automatic identification and setting
- Delivered in a drop-in cassette for easy handling
- Ribbon saver for monochrome printing

List of ribbons available on www.evolis.com

Software & applications



- CardPresso XXS Lite for designing and printing badges. Compatible for Windows® and Mac.

OS compatibility details available on www.cardpresso.com

- Evolis Premium Suite for complete printer management (printer drivers, printer administration and settings, user notifications). Compatible for Windows®.
- Drivers for Mac OS and Linux.
- Evolis Print Service (printing plugin) for printing from Android mobile devices.

OS compatibility details available on www.evolis.com

- Evolis SDK (Software Development Kit) for complete management and optimal integration of Evolis printers in IT applications and systems.

Eco-Friendly Design, Certifications and Statement of Compliance

- Standby, sleep modes & reduced energy consumption
- CE, FCC, IEC, VCCI, CCC, KC, BIS, EAC
- RoHS

Size & Weight


- Size (H x W x D): 195 x 205 x 315 mm (7.68" x 8.07" x 12.4")
- Weight: 3.3 kg (7.3 lbs)

Warranty

- 2-year warranty (printer and print head)⁴
- Warranty extension available as an option

¹ Under specific conditions / ² Depends on the Windows® version / ³ Requires the .net 4.0 client profile version
⁴ Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons





evolIS

Identify what matters

A GLOBAL PROVIDER OF IDENTIFICATION SOLUTIONS

- **Worldwide leader** in card personalization systems for decentralized issuance
- **International expertise and local support** through a network of 400 distributors in 140 countries
- A unique ability to meet specific customer specifications with a **Project department dedicated to design and construction of tailor-made solutions**
- **Evolis is ISO 9001 certified**, which reflects our comprehensive approach, both in terms of quality and continuous improvement

www.evolis.com

HQ / EUROPE - MIDDLE-EAST - AFRICA

Evolis - 14 avenue de la Fontaine - ZI Angers-Beaucouzé
49070 - Beaucouzé - FRANCE
T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

USA - CANADA

Evolis Inc. - Providence - RI - USA - evolisinc@evolis.com

LATIN AMERICA

Evolis Inc. - Fort Lauderdale - FL - USA - evolisinc@evolis.com

ASIA - PACIFIC

Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

CHINA

Evolis China - Shanghai - evolischina@evolis.com

INDIA

Evolis India - Mumbai - evolisindia@evolis.com